Feature	Old Korniche Lantern	Korniche Roof Lantern 2.0	What It Means for Trade Customers
Glazing thickness	24mm double glazed	28mm double glazed	Better insulation, more energy efficient.
Sightlines	Slim aluminium rafters	Slimmer, banked side walls + caps aligned with beams	Wider uninterrupted sky views = big selling point.
Thermal breaks	Polyamide breaks	PVC structural thermal breaks + glazing isolation shoe	Stronger thermal performance for Part L compliance.
Sealing	Q-Lon seals + glass lock	Overlapping injection moulded seals + corner key with silicone port	Perfect sealing, no messy corner work, tighter seal.
Installation	Fast kit build, no cutting	Unique spider tensioning system (2 screws for spider, 6 total) + no roof flipping needed	Faster, cleaner, less hassle – saves time on site.
Aesthetics	Sculpted caps, Victorian-inspired	Contemporary one-piece end caps, cleaner modern finish	Meets modern design trends.
Security	Glass lock	PAS24 security as standard	Peace of mind, meets building regs.
Shut-lines	Standard	Unique tensioning system pulls tighter shut-lines	Cleaner intersections, neater finish.
Inherited benefits	Strong, weather-tight, good looks	Retains all the above + Korniche DNA curves	Same trusted performance, just smarter.
Warranty	10 years	10 years (same coverage)	Still backed by Korniche quality.