SMART ECO FUTURAL - TILT AND TURN WINDOWS

COMMERICAL WINDOWS SUITABLE FOR COMMERICAL, RETAIL, RESIDENTIAL, PUBLIC, HEALTHCARE & EDUCATIONAL APPLICATIONS

95 MM
TYPICAL SIGHTLINE

90KG

TILT TURN MAX. WEIGHT OVERALL.

PIVOT MAX. WEIGHT HORIZONTAL = 180KG

PIVOT MAX. WEIGHT VERTICAL = 120KG

U-VALUE **1.4** W/M²K
USING 1.1 SEALED UNIT.
1.1 W/M²K USING TRIPLE GLAZED 0.6 UNIT

MIN. WIDTH = 402MM
MAX. WIDTH = 1700MM
(AT 1700MM WIDE, MAX. HEIGHT IS 2100MM)

MIN. HEIGHT = 500MM
MAX. HEIGHT = 2400MM

(AT 2400MM HIGH, MAX WIDTH IS 1400MM)

* WIDTH OF TILT/TURN SASH MUST NOT EXCEED 1 1/2 TIMES THE HEIGHT

GLAZING 13MM-60MM
(SASH)
GLAZING 4MM-51MM
(OUTER FRAME)

ALL PROFILES FEATURE POLYAMIDE BREAK THAT ENHANCES THERMAL PROPERTIES

FRAME DEPTH	WER	AIR	WIND	WATER	PAS	DOC. L
65MM	A	600PA	2400PA	900 PA	24:2016	COMPLIANT

SMART ECO FUTURAL - TILT AND TURN WINDOWS